

BS4518 Size Chart

1.6MM CROSS SECTION +/- 0.08MM			
BS4518 REF	SIZE REF	INSIDE DIAMETER MM	INSIDE DIAMETER TOL +/-
0031-16	202-505	3.1	0.15
0041-16	202-506	4.1	
0051-16	202-507	5.1	
0061-16	202-508	6.1	
0071-16	202-509	7.1	
0081-16	202-510	8.1	
0091-16	202-511	9.1	
0101-16	202-512	10.1	0.2
0111-16	202-513	11.1	
0121-16	202-514	12.1	
0131-16	202-515	13.1	
0141-16	202-516	14.1	
0151-16	202-517	15.1	
0161-16	202-518	16.1	
0171-16	202-519	17.1	
0181-16	202-520	18.1	0.25
0191-16	202-521	19.1	
0221-16	202-524	22.1	
0251-16	202-525	25.1	
0271-16	202-526	27.1	
0291-16	202-527	29.1	
0321-16	202-528	32.1	0.3
0351-16	202-529	35.1	
0371-16	202-530	37.1	

BS4518 Size Chart

2.4MM CROSS SECTION +/- 0.08MM			
BS4518 REF	SIZE REF	INSIDE DIAMETER MM	INSIDE DIAMETER TOL +/-
0036-24	202-630	3.6	0.15
0046-24	202-631	4.6	
0056-24	202-632	5.6	
0066-24	202-633	6.6	
0076-24	202-634	7.6	
0086-24	202-635	8.6	
0096-24	202-636	9.6	
0106-24	202-637	10.6	0.2
0116-24	202-638	11.6	
0126-24	202-639	12.6	
0136-24	202-640	13.6	
0146-24	202-641	14.6	
0156-24	202-642	15.6	
0166-24	202-643	16.6	
0176-24	202-644	17.6	0.25
0186-24	202-645	18.6	
0196-24	202-646	19.6	
0206-24	202-670	20.6	
0216-24	202-647	21.6	
0246-24	202-648	24.6	
0276-24	202-649	27.6	
0296-24	202-650	29.6	0.3
0316-24	202-651	31.6	
0346-24	202-652	34.6	
0356-24	202-672	35.6	
0376-24	202-653	37.6	
0396-24	202-654	39.6	
0416-24	202-655	41.6	
0446-24	202-656	44.6	0.3
0456-24	202-673	45.6	

BS4518 Size Chart

BS4518 REF	SIZE REF	INSIDE DIAMETER MM	
0476-24	202-657	47.6	0.3
0496-24	202-658	49.6	
0516-24	202-659	51.6	0.4
0546-24	202-660	54.6	
0556-24	202-674	55.6	
0576-24	202-661	57.6	
0586-24	202-675	58.6	
0596-24	202-662	59.6	
0616-24	202-663	61.6	
0626-24	202-676	62.6	
0646-24	202-664	64.6	
0676-24	202-665	67.6	
0696-24	202-666	69.6	

BS4518 Size Chart

3.0MM CROSS SECTION +/- 0.1MM			
BS4518 REF	SIZE REF	INSIDE DIAMETER MM	INSIDE DIAMETER TOL +/-
0195-30	202-771	19.5	0.25
0215-30	202-772	21.5	
0225-30	202-773	22.5	
0245-30	202-774	24.5	
0255-30	202-775	25.5	
0265-30	202-776	26.5	
0275-30	202-777	27.5	
0295-30	202-778	29.5	
0315-30	202-779	31.5	0.3
0325-30	202-780	32.5	
0345-30	202-781	34.5	
0355-30	202-782	35.5	
0365-30	202-783	36.5	
0375-30	202-784	37.5	
0395-30	202-785	39.5	
0415-30	202-786	41.5	
0425-30	202-787	42.5	
0445-30	202-788	44.5	
0495-30	202-729	49.5	0.4
0545-30	202-731	54.5	
0555-30	202-790	55.5	
0575-30	202-791	57.5	
0595-30	202-735	59.5	
0625-30	202-792	62.5	
0645-30	202-738	64.5	
0695-30	202-739	69.5	
0745-30	202-740	74.5	0.5
0795-30	202-741	79.5	
0845-30	202-742	84.5	
0895-30	202-743	59.5	

BS4518 Size Chart

BS4518 REF	SIZE REF	INSIDE DIAMETER MM	INSIDE DIAMETER TOL +/-
0945-30	202-744	94.5	0.50
0995-30	202-745	99.5	
1045-30	202-746	104.5	
1095-30	202-747	109.5	
1145-30	202-748	114.5	
1195-30	202-749	119.5	
1245-30	202-750	124.5	0.6
1295-30	202-751	129.5	
1345-30	202-752	134.5	
1395-30	202-753	139.5	
1445-30	202-754	144.5	
1495-30	202-755	149.5	
1545-30	202-756	154.5	
1595-30	202-757	159.5	
1645-30	202-758	164.5	
1695-30	202-759	169.5	
1745-30	202-760	174.5	
1795-30	202-761	179.5	0.8
1845-30	202-762	184.5	
1895-30	202-763	189.5	
1945-30	202-764	194.5	
1995-30	202-765	199.5	
2095-30	202-789	209.5	
2195-30	202-767	219.5	
2295-30	202-768	229.5	
2395-30	202-769	239.5	
2445-30	202-793	244.5	
2495-30	202-770	249.5	

BS4518 Size Chart

5.7MM CROSS SECTION (0.224 INCHES)			
BS4518 REF	SIZE REF	INSIDE DIAMETER MM	INSIDE DIAMETER TOL +/-
0443-57	202-810	44.3	0.3
0453-57	202-811	45.3	
0493-57	202-813	49.3	
0523-57	202-815	52.3	
0543-57	202-816	54.3	
0553-57	202-879	55.3	
0593-57	202-818	59.3	0.40
0623-57	202-820	62.3	
0643-57	202-821	64.3	
0693-57	202-823	69.3	
0743-57	202-826	74.3	
0793-57	202-828	79.3	
0843-57	202-831	84.3	
0893-57	202-833	89.3	
0943-57	202-835	94.3	
0993-57	202-837	99.3	
1043-57	202-838	104.3	
1093-57	202-839	109.3	
1143-57	202-840	114.3	
1193-57	202-841	119.3	
1243-57	202-842	124.3	
1293-57	202-843	129.3	
1343-57	202-844	134.3	
1393-57	202-845	139.3	
1443-57	202-846	144.3	0.60
1493-57	202-847	149.3	
1543-57	202-848	154.3	
1593-57	202-849	159.3	
1643-57	202-850	164.3	
1693-57	202-851	169.3	

BS4518 Size Chart

BS4518 REF	SIZE REF	INSIDE DIAMETER MM	INSIDE DIAMETER TOL +/-
1743-57	202-852	174.3	0.6
1793-57	202-853	179.3	
1843-57	202-854	184.3	
1893-57	202-855	189.3	
1943-57	202-856	194.3	
1993-57	202-857	199.3	
2093-57	202-859	209.3	
2193-57	202-860	219.3	
2293-57	202-861	229.3	
2393-57	202-862	239.3	
2493-57	202-863	249.3	
2593-57	202-864	259.3	
2693-57	202-865	269.3	
2793-57	202-866	279.3	
2893-57	202-867	289.3	
2993-57	202-868	299.3	
3093-57	202-890	309.3	
3193-57	202-869	319.3	
3393-57	202-870	339.3	
3593-57	202-871	359.3	1.5
3793-57	202-872	379.3	
3893-57	202-891	389.3	
3993-57	202-873	399.3	
4193-57	202-874	419.3	
4393-57	202-875	439.3	
4593-57	202-876	459.3	
4793-57	202-877	479.3	
4893-57	202-892	489.3	
4993-57	202-878	499.3	

BS4518 Size Chart

8.4MM CROSS SECTION +/- 0.15MM			
BS4518 REF	SIZE REF	INSIDE DIAMETER MM	INSIDE DIAMETER TOL +/-
1441-84	202-905	144.1	0.6
1491-84	202-906	149.1	
1541-84	202-907	154.1	
1591-84	202-908	159.1	
1641-84	202-909	164.1	
1691-84	202-910	169.1	
1741-84	202-911	174.1	
1791-84	202-912	179.1	
1841-84	202-913	184.1	0.80
1891-84	202-914	189.1	
1941-84	202-915	194.1	
1991-84	202-916	199.1	
2041-84	202-922	204.1	
2091-84	202-917	209.1	
2191-84	202-918	219.1	
2291-84	202-919	229.1	
2341-84	202-923	234.1	
2391-84	202-920	239.1	
2491-84	202-921	249.1	